



**AIR CONDITIONING**  
*GARAGE EQUIPMENT*







**WERTHER INTERNATIONAL SpA**

via Brunelleschi 12, - 42124 Reggio Emilia ITALY

Tel. +39 0522 9431 / +39 346 98 37 325 / +39 346 98 37 443

Fax +39 0522 941997

info@wertherint.com

[www.wertherint.com](http://www.wertherint.com)

# AC 930.19

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant
- Oil and tracer



**GAS**  
**R 134-A**



CE | EAC

## TECHNICAL DATA

Vacuum Pump	3 CFM
Vacuum	4X10 <sup>-2</sup> mbar
Compressor Power	0,33 KW
Stockage Cylinder	12 Lt
Resolution gas scale	10 g
Display	2 x 16 LCD
Languages	13
Recovery rate	330 g/min
Charging Hoses	180 cm
Leakage detection	YES
Printer	Optional
Keyboard	7 keys
Gauges	80 mm
Cylinder gauges	YES
Heater	Optional
Filter driers	1
Tracer	Optional
Voltage	230/50 1 ph

## ACCESSORIES



**P.N 1697000026**  
Blue pipe 5m



**P.N 1697000030**  
Red pipe 5m



**P.N 1697000029**  
Tracer



**P.N 1697000027**  
Printer



**P.N 1697000028**  
Leakage detector

## FEATURES



CD display with instructions available in 13 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, POSSIBILITY Serbian and Croatian



Full automatic operations



Data bank as a standard



Automatic control of leaks



12 liters tank.



Top precision thanks to its 24 bit analogical digital converter



Electronic gas scale



180 cm pipes as a standard.

# AC 930.19 NG

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant
- Oil and tracer



**GAS**  
**R 1234-YF**




CE | EAC









## TECHNICAL DATA

Vacuum Pump	3 CFM
Recovery rate	330 g/min
Vacuum	4X10 <sup>-2</sup> mbar
Stockage Cylinder	12 Lt
Resolution gas scale	10 g
Resolution oil scale	1 temp.
Display	16 X 2 lcd.
Languages	13
Charging Hoses	180 cm
Leakage detection	YES
Printer	Optional
Gauges	80 mm
Cylinder gauges	YES
Heater	Optional
Filter driers	1
Tracer	Optional
Voltage	230/50 1 ph

## ACCESSORIES



## FEATURES

-  CD display with instructions available in 13 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, POSSIBILITY Serbian and Croatian
-  Full automatic operations
-  Data bank as a standard
-  Automatic control of leaks
-  12 liters tank
-  Top precision thanks to its 24 bit analogical digital converter
-  Electronic gas scale
-  180 cm pipes as a standard

# AC 930.19 LIGHT - AC 930.19 LIGHT P

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant
- Oil and tracer



**GAS**  
**R 134-A**



*LIGHT P: printer as a standard*

CE | EAC



## TECHNICAL DATA

Vacuum Pump	2 CFM
Vacuum	4X10 <sup>-2</sup> mbar
Recovery rate	280 g/min.
Stockage Cylinder	12 Lt
Resolution gas scale	10 g
Resolution oil scale	1 temp.
Display	2 x 16 LCD
Languages	13
Charging Hoses	180 cm
Leakage detection	YES
Printer	Optional (YES-Light P)
Gauges	63 mm
Cylinder gauges	YES
Heater	Optional
Filter driers	1
Tracer	Optional
Gas Analyzer	NO
Voltage	230/50 1 ph

## ACCESSORIES



**P.N 1697000026**  
Blue pipe 5 m



**P.N 1697000030**  
Red pipe 5 m



**P.N 1697000029**  
Tracer











**P.N 1697000027**  
Printer  
(only for Tec 20 light)



**P.N 1697000028**  
Leakage detector

## FEATURES

-  CD display with instructions available in 13 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, POSSIBILITY Serbian and Croatian
-  Full automatic operations
-  Data bank as a standard
-  Automatic control of leak
-  12 liters tank
-  Electronic gas scale
-  180 cm pipes as a standard
-  Top precision thanks to its 24 bit analogical digital converter

# AC 930.15.CO

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scale for refrigerant



**GAS**  
**R 134-A**



CE | EAC









## TECHNICAL DATA

Vacuum Pump	3 CFM
Vacuum	4X10 <sup>-2</sup> mbar
Compressor power	0,33 KW
Stockage Cylinder	12 Lt
Resolution gas scale	10 g
Recovery rate	330 g/min
Charging Hoses	180 cm
Dimensions	42x52x107 cm
Gross Weight	72 kg
Display	2x16 LCD
Gauges	63mm
Tracer	Optional
Leakage detection	YES
Cylinder gauges	YES
Voltage	230V - 50 Hz - 1ph

## ACCESSORIES



## FEATURES

-  CD display with instructions available in 13 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, POSSIBILITY Serbian and Croatian
-  Full automatic operations
-  Data bank as a standard
-  Automatic control of leaks
-  12 liters tank
-  Electronic gas scale
-  Top precision thanks to its 24 bit analogical digital converter
-  180cm pipes as a standard

# AC 960.15

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant
- Oil and tracer



**GAS**  
**R 134-A**



CE | EAC

## TECHNICAL DATA

Vacuum pump	4 CFM
Vacuum	4X10 <sup>-2</sup> mbar
Compressor power	0,25 KW
Storage Cylinder	22 Lt
Gas scale accuracy	+/- 1 g
Oil scale accuracy	+/- 1 g
Recovery rate	330 g/min
Charging pipes	300 cm
Size	55x57x122 cm
Gross weight	80 kg
USB	YES
Tracer	Optional
Leackage detector	YES
Cylinder manometer	YES
Voltage	230V - 50 Hz - 1ph

## ACCESSORIES



## FEATURES

- LCD display with instructions available in 15 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, Serbian and Croatian
- Full automatic operations
- Vehicles data base, possibility to add 200 new vehicles, thermal printer with roll as a standard
- Thermal printer with roll as a standard
- Automatic control of leaks
- 22 liters tank
- Top precision thanks to its 24 bit analogical digital converter
- 300 cm pipes as a standard
- Possibility of cycles storage on a USB flash drive

# AC 1000.15

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant
- Oil and tracer



**GAS**  
**R 1234-YF**



CE | EAC

## TECHNICAL DATA

Vacuum pump	4 CFM
Vacuum	4X10 <sup>-2</sup> mbar
Compressor power	0,33 KW
Storage Cylinder	22 Lt
Gas scale accuracy	1 g
Oil scale accuracy	1 g
Recovery rate	330 g/min
Charging pipes	300 cm
Size	55x57x122 cm
Gross weight	80 kg
USB	YES
Tracer	Optional
Leackage detector	YES
Cylinder manometer	YES
Voltage	230V - 50 Hz - 1ph

## ACCESSORIES



**P.N 1697000031**  
Blue pipe 5 m



**P.N 1697000032**  
Red pipe 5 m













**P.N 1697000029**  
Tracer



**P.N 1697000028**  
Leakage detector

## FEATURES

-  LCD display with instructions available in 15 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, Serbian and Croatian
-  Full automatic operations
-  Vehicles data base, possibility to add 200 new vehicles
-  Thermal printer with roll as a standard
-  Automatic control of leaks
-  22 liters tank
-  Top precision thanks to its 24 bit analogical digital converter
-  300 cm pipes as a standard
-  Possibility of cycles storage on a USB flash drive
-  Its metal body conveys the unit a great robustness

# FR 3002/S

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant and oil. Suitable for big circuits



**GAS**  
**R 134-A**



CE | EAC



## TECHNICAL DATA

Vacuum pump	7 CFM
Storage Cylinder	40 Lt
Recovery rate	400 g/min
Charging pipes	300 cm
Size	45x95x127 cm
Gross Weight	127 kg
Manometer	63mm
Tracer	Optional
Leaks detector	YES
Cylinder Manometer	YES
Voltage	230V - 50 Hz - 1ph

## ACCESSORIES



**P.N 1697000026**  
Blue pipe 5 m



**P.N 1697000030**  
Red pipe 5 m










**P.N 1697000029**  
Tracer



**P.N 1697000028**  
Leakage detector

## FEATURES

-  LCD display with instructions available in 13 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, POSSIBILITY Serbian and Croatian.
-  Full automatic operations
-  Cars, buses, tractors, trucks data base, as a standard
-  Automatic control of leaks
-  40 liters tank
-  Top precision thanks to its 24 bit analogical digital converter
-  300 cm pipes as a standard



Via F. Brunelleschi, 12 - 42124 Cadè (RE) Italy  
Tel. +39 0522 9431 +39 346 98 37 325 +39 98 37 443  
Fax + 39 0522 941997 • E-mail: [sales@wertherint.com](mailto:sales@wertherint.com)  
**wertherint.com**