

AC 930.19 LIGHT - AC 930.19 LIGHT P

WERTHER AIR CONDITIONING

- Automatic unit for recovery
- Vacuum and recharge with electronic scales for refrigerant
- Oil and tracer



GAS
R 134-A



LIGHT P: printer as a standard

CE | EAC

TECHNICAL DATA

| | |
|----------------------|-------------------------|
| Vacuum Pump | 2 CFM |
| Vacuum | 4X10 ⁻² mbar |
| Recovery rate | 280 g/min. |
| Stockage Cylinder | 12 Lt |
| Resolution gas scale | 10 g |
| Resolution oil scale | 1 temp. |
| Display | 2 x 16 LCD |
| Languages | 13 |
| Charging Hoses | 180 cm |
| Leakage detection | YES |
| Printer | Optional (YES-Light P) |
| Gauges | 63 mm |
| Cylinder gauges | YES |
| Heater | Optional |
| Filter driers | 1 |
| Tracer | Optional |
| Gas Analyzer | NO |
| Voltage | 230/50 1 ph |

ACCESSORIES



P.N 1697000026
Blue pipe 5 m



P.N 1697000030
Red pipe 5 m



P.N 1697000029
Tracer



P.N 1697000027
Printer
(only for Tec 20 light)



P.N 1697000028
Leakage detector

FEATURES

-  CD display with instructions available in 13 different languages. Italian, English, French, Spanish, German, Portuguese, Turk, Polish, Hungarian, Dutch, Swedish, Russian, Estonian, POSSIBILITY Serbian and Croatian
-  Full automatic operations
-  Data bank as a standard
-  Automatic control of leak
-  12 liters tank
-  Electronic gas scale
-  180 cm pipes as a standard
-  Top precision thanks to its 24 bit analogical digital converter